



## F75FETL

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



### TECHNICAL CHARACTERISTICS

### F75FETL

#### MOTOR

Displacement (cc)	1832
Full throttle operating range (tr/min)	5000-6000
Fuel	Unleaded Gasoline
Fuel consumption (L/h-tr/min)	28.7 L/h @6000 r/min
Lubrication system	Wet sump
Power system	Electronic Fuel Injection (EFI)
Bore x Stroke (mm)	81.0 X 88.9
Architecture	In-line
Reverse direction	No
Steering Control	Remote control
Gear Ratio	2.15 (28/13)
Trim method (positions)	Power Trim & Tilt
Ignition System	TCI
Maximum Power (Kw)	55.2
Number of Displacement	4-cylinder
Reduction ratio	10.0 :1
Starter system	Electric
Engine Type	4-stroke
Max.Prop Shaft Horsepower (Kw)	N/A

#### MORE

Alternator	35A
Propeller Rotation	Clockwise (Standard)

#### DIMENSIONS

Engine Oil Capacity (L)	3.2
Oil capacity (L)	0.760
Engine transom height (mm)	X : 643 (25.3 inch)
Dry weight with propeller (kg)	162

Always wear a helmet, eye protection and protective proper clothing.

encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

